

ROYALOHM

C O N F I D E N T I A L D O C U M E N T

SPECIFICATION FOR APPROVAL

TRELIK

Description : Thick Film Chip Resistors (Terminal Lead Free)

Royalohm Part no.:

25121WxxxxT4E (RMC 1W (2512) +/-1%, 5% & Jumper)

Approved by

Parts corresponding to RoHS Compliant: 2005-Apr.-1

Royal Electronic Factory (Thailand) Co., Ltd.

20/1-2 Moo 2 Klong-Na, Muang

Chachoengsao 24000, Thailand

Tel: +66-38-822404-8

Fax: +66 38-981190 / 823765

E-mail Address: Export sales: Export@royalohm.com

Local sales: Local@royalohm.com

<http://www.royalohm.com>

P.O. Box 251 Klongchan, Bangkok 10240, Thailand

| Approved | Checked | Prepared |
|--------------|--------------------|----------------|
| Mr. Jack Lin | Mr. S. Polthanasan | Ms. P. Supatta |

Issue Date: 2015/01/10

| | |
|-------------------------|---------------------------------|
| Customer: TRELIK | Part. No.: 25121WxxxxT4E |
|-------------------------|---------------------------------|

1. Scope:

This specification for approval relates to Thick Film Chip Resistors (Terminal Lead Free) manufactured by ROYALOHM 's specifications.

2. Type designation:

The type designation shall be in the following form:

| | Type | Power Rating | Resistance tolerance | Nominal Resistance |
|------------|----------|--------------|----------------------|--------------------|
| <u>Ex.</u> | RMC 2512 | 1W | F, J | 1KΩ |


3. Ratings:

| | |
|---------------------------------|----------------|
| Type | RMC 2512 |
| Power Rating | 1W |
| Rated Current (Jumper) | 2.5A |
| Max. Overload Current (Jumper) | 10A |
| Max. Working Voltage | 200 V |
| Max. Overload Voltage | 500 V |
| Dielectric Withstanding Voltage | 500 V |
| Temperature Range | -55°C ~ +155°C |
| Ambient Temperature | 70 °C |

3.1 Power rating:

Resistors shall have a power rating based on continuous load operation at an ambient temperature of 70 °C . For temperature in excess of 70 °C , The load shall be derate as shown in figure 1.

Figure 1




3.2 Nominal Resistance


Effective figures of nominal resistance shall be in accordance with E-24 and E-96 series. E-96 series for 1% and E-24 series for 2%, 5%.

Thick Film Chip Resistors (Terminal Lead Free)

4. Construction :



5. Power rating and dimensions



Dimension :

| Type | Dimension (mm) | | | | |
|----------|----------------|--------------|--------------|----------------|----------------|
| | $L \pm 0.10$ | $W \pm 0.15$ | $H \pm 0.10$ | $l_1 \pm 0.25$ | $l_2 \pm 0.20$ |
| RMC 2512 | 6.35 | 3.20 | 0.55 | 0.60 | 0.50 |

Power Rating :

| Type | Power Rating at 70 °C | Tolerance % | Resistance Range | Standard Series |
|----------|-----------------------|-------------|------------------|-----------------|
| RMC 2512 | 1W | Jumper | < 50mΩ | |
| | | ± 1 | 10Ω ~ 1MΩ | E-96 |
| | | ± 5 | 1Ω ~ 10MΩ | E-24 |

Thick Film Chip Resistors (Terminal Lead Free)

6. Marking :

6.1 Resistors

A. Marking for E-96 series in 2512 size : 4 Digits

*The first 3 digits are significant figures of resistance and the 4th digit denoted number of zeros.

| | | |
|-----|------|---------------|
| Ex. | 1003 | 100K Ω |
|-----|------|---------------|

*For ohmic values below 100 Ω , letter "R" is for decimal point.

| | | |
|-----|------|--------------|
| Ex. | 1R80 | 1.8 Ω |
|-----|------|--------------|

B. Marking for E-24 series in 2512 size : 3 Digits

*The first 2 digits are significant figures of resistance and the 3rd digit denoted number of zeros.

| | | |
|-----|-----|-------------|
| Ex. | 102 | 1K Ω |
|-----|-----|-------------|

*For ohmic values below 10 Ω , letter "R" is for decimal point.


| | | |
|-----|-----|---------------|
| Ex. | R68 | 0.68 Ω |
|-----|-----|---------------|

6.2 Labels

Label shall be marked with the following item :

- A. Nominal Resistance and Resistance Tolerance
- B. Power Rating and Size
- C. Quantity
- D. Part No.
- E. P.O.No.
- F. Lot No.


Ex.

| | | |
|--|-----------------------|-------------|
| ROYALOHM | | |
| Chip Resistors | | |
| Resistance : | 1K Ω | \pm 5% |
| Wattage : | 1W | Size : 2512 |
| Quantity : | 4000 Pcs. | 100 PPM |
| Part No.: | | |
| Lot No. : | 825723 25121WJ0102T4E | |
|  | | |

Remark : Label is 1K, value is 1K Ω , marking is 102

Thick Film Chip Resistors (Terminal Lead Free)

7. Performance specification :


| Characteristics | Limits | Test Methods (JIS C 5201-1) |
|----------------------------------|--|--|
| *Insulation resistance | 1,000 MΩ or more | Apply 500V DC between protective coating and termination for 1 min, then measure (Sub-clause 4.6) |
| *Dielectric withstanding voltage | No evidence of flashover mechanical damage, arcing or insulation break down | Apply 500V AC between protective coating and termination for 1 minute (Sub-clause 4.7) |
| Temperature coefficient | 1Ω-10Ω : ± 400 PPM/°C 11Ω-100Ω : ± 200 PPM/°C >100Ω : ± 100 PPM/°C | Natural resistance change per temp. degree centigrade. $\frac{R_2 - R_1}{R_1(t_2 - t_1)} \times 10^6 \text{ (PPM/°C)}$ R1: Resistance value at room temperature (t1) R2: Resistance value at room temp. plus 100 °C (t2) (Sub-clause 4.8) |
| Short time overload | Resistance change rate is ± 5% (2.0% + 0.1 Ω) Max. ± 1% (1.0% + 0.1 Ω) Max. | Permanent resistance change after the application of a potential of 2.5 times RCWV for 5 seconds (Sub-clause 4.13) |
| *Solderability | 95 % coverage Min. | Test temperature of solder : 245 ± 3°C Dipping them solder : 2-3 seconds (Sub-clause 4.17) |
| Soldering temp. reference | Electrical characteristics shall be satisfied. Without distinct deformation in appearance. (95 % coverage Min.) | <p><u>Wave soldering condition:</u> (2 cycles Max.) Pre-heat : 100 ~ 120 °C, 30 ± 5 sec. Suggestion solder temp.: 235 ~ 255 °C, 10 sec. (Max.) Peak temp.: 260 °C</p> <p><u>Reflow soldering condition:</u> (2 cycles Max.) Pre-heat : 150 ~ 180 °C, 90 ~ 120 sec. Suggestion solder temp.: 235 ~ 255 °C, 20 ~ 40 sec. Peak temp.: 260 °C</p>  <p><u>Hand soldering condition:</u> The soldering iron tip temperature should be less than 300°C and maximum contact time should be 5 sec.</p> |

| Thick Film Chip Resistors (Terminal Lead Free) | | | | |
|---|---|--|--|-------------|
| 7. Performance specification : | | | | |
| Characteristics | Limits | Test Methods (JIS C 5201-1) | | |
| Soldering Heat | Resistance change rate is: $\pm(1\%+0.05\Omega)$ Max. | Dip the resistor into a solder bath having a temperature of $260^{\circ}\text{C}\pm 3^{\circ}\text{C}$ and hold it for 10 ± 1 seconds. (Sub-clause 4.18) | | |
| Temperature cycling | Resistance change rate is $\pm 5\%$ ($1.0\% + 0.05 \Omega$) Max. $\pm 1\%$ ($0.5\% + 0.05 \Omega$) Max. | Resistance change after continuous 5 cycles for duty cycle specified below : | | |
| | | Step | Temperature | Time |
| | | 1 | $-55^{\circ}\text{C} \pm 3^{\circ}\text{C}$ | 30 mins |
| | | 2 | Room temp. | 10~15 mins |
| | | 3 | $+155^{\circ}\text{C} \pm 2^{\circ}\text{C}$ | 30 mins |
| | | 4 | Room temp. | 10~15 mins |
| | | (Sub-clause 4.19) | | |
| Load life in humidity | Resistance change rate is $\pm 5\%$ ($3.0\% + 0.1 \Omega$) Max. $\pm 1\%$ ($1.0\% + 0.1 \Omega$) Max. | Resistance change after 1,000 hours (1.5 hours "on", 0.5 hour "off") at RCWV in a humidity chamber controlled at $40^{\circ}\text{C} \pm 2^{\circ}\text{C}$ and 90 to 95 % relative humidity (Sub-clause 4.24.2.1) | | |
| Load Life | Resistance change rate is $\pm 5\%$ ($3.0\% + 0.1 \Omega$) Max. $\pm 1\%$ ($1.0\% + 0.1 \Omega$) Max. | Permanent resistance change after 1,000 hours operating at RCWV, with duty cycle of (1.5 hours"on", 0.5 hour"off") at $70^{\circ}\text{C} \pm 2^{\circ}\text{C}$ ambient (Sub-clause 4.25.1) | | |
| Terminal bending | Resistance change rate is $\pm (1.0\% + 0.05 \Omega)$ Max. | Twist of Test Board : $Y/X = 5/90$ mm for 10 seconds (Sub-clause 4.33) | | |
| The resistors of 0Ω only can do the characteristic noted of * | | | | |

Thick Film Chip Resistors (Terminal Lead Free)

8. Packing specification :


* Taping Dimension (mm)




| Type | A ±0.2 | B ±0.2 | C ±0.05 | $\phi D+0.1$ -0 | E ±0.1 | F ±0.05 | G ±0.1 | W ±0.2 | $\phi D1+0.1$ -0 | T ± 0.1 |
|------|--------|--------|---------|--------------------|--------|---------|--------|--------|---------------------|---------|
| 2512 | 3.5 | 6.7 | 2.0 | 1.5 | 1.75 | 5.5 | 4.0 | 12 | 1.5 | 1.0 |

* Peeling Strength of Top Cover Tape

Test Condition: 0.1 to 0.7 N at a peel-off speed of 300 mm / min.



* Reel Dimension (mm)




| Type | Quantity Per Reel | A ± 0.5 | B ± 0.5 | C ± 0.5 | D ± 1 | M ± 2 | W ± 1 |
|------|-------------------|---------|---------|---------|-------|-------|-------|
| 2512 | 4000 Pcs. Reel | 2 | 13 | 21 | 60 | 178 | 13.8 |

Part Number System

Explanation of Part Number System

Thick Film Chip Resistors (Terminal Lead Free)



Product Type:
 Fill-in these 4 digits with the Chip resistor types as follows:
 0402
 0603
 0805
 1206
 1210
 2010
 2512

Wattage:
 Fill-in these 2 digits with the codes as follows:
Normal size:
 WG = 1/16W
 WA = 1/10W
 W8 = 1/8W
 W4 = 1/4W
 W2 = 1/2W
 1W = 1W
Small size:
 SA = 1/10W-S
 S8 = 1/8W-S
 S4 = 1/4W-S
 S3 = 1/3W-S
 07 = 3/4W-S
Special:
 WH = 1/32W

Tolerance:
 F ~ ± 1%
 G ~ ± 2%
 J ~ ± 5%

Resistance Value:
 1. E-24 series: the 1st digit is "0", the 2nd & 3rd digits are for the significant figures of the resistance and the 4th indicate the number of zeros following;
 2. E-96 series: the 1st to 3rd digits are for the significant figures of the resistance and the 4th digit indicate the number of zeros following.
 Decimal point is expressed :
 "J"~ 0.1, "K"~0.01, "L"~0.001
 Ex: 2Ω26 ~226K, 226Ω ~2260

Packing Quantity:
 1 = 1,000pcs
 2 = 2,000pcs
 3 = 3,000pcs
 4 = 4,000pcs
 5 = 5,000pcs
 A = 500pcs
 B = 2,500pcs
 C = 10,000pcs
 D = 20,000pcs
 E = 15,000pcs
 G = 25,000pcs
 H = 50,000pcs

Packing Type:
 T = T/R Packing
 B = Bulk in Poly-bag
 C = Bulk in cassette

Special Feature:
 0 = NIL
 E = Lead Free

Sample :
 RMC 1W (2512) +/- 5% 1KΩ T/R--4,000 → 25121WJ0102T4E
 RMC 1W (2512) +/- 5% 0Ω T/R--4,000 → 25121WJ0000T4E
 RMC 1W (2512) +/- 1% 1KΩ T/R--4,000 → 25121WF1001T4E

Thick Film Chip Resistors (Terminal Lead Free)

Environment Related Substance

This product complies to EU RoHS directive, EU PAHs directive, EU PFOS directive and Halogen free.

Ozone layer depleting substances.

Ozone depleting substances are not used in our manufacturing process of this product.

This product is not manufactured using Chloro fluorocarbons (CFCs), Hydrochlorofluorocarbons (HCFCs), Hydrobromofluorocarbons (HBFCs) or other ozone depleting substances in any phase of the manufacturing process.

Storage Condition

The performance of these products, including the solderability, is guaranteed for a year from the date of arrival at your company, provided that they remain packed as they were when delivered and stored at a temperature of $25^{\circ}\text{C} \pm 5^{\circ}\text{C}$ and a relative humidity of $60\%\text{RH} \pm 10\%\text{RH}$

Even within the above guarantee periods, do not store these products in the following conditions. Otherwise, their electrical performance and/or solderability may be deteriorated, and the packaging materials (e.g. taping materials) may be deformed or deteriorated, resulting in mounting failures.

1. In salty air or in air with a high concentration of corrosive gas, such as Cl_2 , H_2S , NH_3 , SO_2 , or NO_2
2. In direct sunlight